



# AX SERIES

## Aluminum Cargo Trailer

Specifications vary by plant



### STANDARD FEATURES

Optional Equipment May Be Shown

- Aluminum Tube Main Frame
- 24" O.C. Main Frame
- 16" O.C. Sidewalls
- 24" O.C. Roof Bows
- 4-Wheel Electric Brakes (Tandem Axle)
- 15" Radial Tires
- 2" Coupler (Single Axle)
- 2-5/16" Coupler (Tandem Axle)
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" Floor
- 3/8" Walls
- Flat Top Roof with V-Front
- 24" V on 5' & 6' Wides
- 30" V on 7' Wides
- .030 Screwless Exterior Walls
- 1 Piece Aluminum Roof
- ATP Fenders
- 24" ATP Stoneguard
- Single Rear Door on 5' Wides
- Double Rear Doors on 6' and 7' Wides
- 32" Aluminum Framed Door w/Flushlock (6' and 7' Wides)
- (2) Sidewall Vents
- 4-Way Plug (Single Axle)
- 7-Way Plug (Tandem Axle)
- LED Clearance Lights
- LED Tail Lights
- (1) LED Dome Light and Switch
- Limited 3 Year Warranty

[www.cargoexpress.com](http://www.cargoexpress.com)

	<b>AX ALUMINUM CARGO TRAILER</b>					
	ACW5X8SI2	ACW5X10SI2	ACW6X10SI2	ACW6X12SI2	ACW7X14TE2	ACW7X16TE2
Overall Length	141"	165"	171"	195"	220"	244"
Width	82"	82"	93"	93"	102"	102"
Height	87"	87"	93"	93"	94"	94"
Interior Length	9'7"	11'7"	11'7"	13'7"	15'11"	17'11"
Interior Width	56 1/2"	56 1/2"	68"	68"	79"	79"
Interior Height	66"	66"	72"	72"	72"	72"
Platform Height	19"	19"	19"	19"	21"	21"
Rear Opening Ht.	60"	60"	66"	66"	66"	66"
Rear Opening Wd.	53 1/2"	53 1/2"	66"	66"	76"	76"
Hitch Ball Height	19"	19"	19"	19"	21"	21"
Hitch Ball Size	2"	2"	2"	2"	2 5/16"	2 5/16"
Brakes	OPT	OPT	OPT	OPT	ELECTRIC	ELECTRIC
GVWR	2990#	2990#	2990#	2990#	7000#	7000#
Hitch Weight	115#	124#	142#	153#	224#	237#
Curb Weight	954#	1030#	1180#	1272#	1865#	1976#
Payload Capacity	2036#	1960#	1810#	1718#	5135#	5024#
Tires	15"	15"	15"	15"	15"	15"
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE	TUBE
Floor	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Tail Lights	LED	LED	LED	LED	LED	LED
Clearance Lights	LED	LED	LED	LED	LED	LED
Dome Light	STD	STD	STD	STD	STD	STD
Switch	STD	STD	STD	STD	STD	STD
Sidewall Vents	2	2	2	2	2	2
Stone Guard	24"	24"	24"	24"	24"	24"
V-Front	STD	STD	STD	STD	STD	STD
Side Door	OPT	OPT	32"	32"	32"	32"
Rear Door	SINGLE	SINGLE	DOUBLE	DOUBLE	DOUBLE	DOUBLE
Sand Pad	STD	STD	STD	STD	STD	STD
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Crossmembers	24" OC	24" OC	24" OC	24" OC	24" OC	24" OC
Axles	SPRING	SPRING	SPRING	SPRING	SPRING	SPRING
EZ Lube	YES	YES	YES	YES	YES	YES
Undercoat	N/A	N/A	N/A	N/A	N/A	N/A

Specifications Subject to Change Without Notice