



## Pro-GT 8.5' Widebody Race Trailer

Specifications vary by plant



Shown with Optional Spread Axles & other Equipment

### STANDARD FEATURES

- Tube Main Frame Construction
- 16" O.C. Frame
- 16" O.C. Tube Sidewalls
- 16" O.C. Roof Bows
- Torsion Axles
- EZ-Lube Hubs
- 4-Wheel Electric Brakes
- Radial Tires
- 2-5/16" Coupler
- Safety Chains
- 2000# Tongue Jack
- Sand Pad
- 3/4" Floor
- White Vinyl or 3/8" Wall Liner
- White Vinyl Insulated Ceiling Liner
- .040 Screwless Aluminum Exterior
- Two Tone Exterior Available No Charge
- Truck Body Extrusion
- Stainless Steel Front Insert
- Stainless Steel Rear Corners and Header
- Stainless Steel Front Corners
- 1 Piece Aluminum Roof
- Aluminum Fender Flares
- 24" Stoneguard
- Heavy Duty Ramp Door with Spring Assist & 16" Ramp Door Extension
- Recessed Horizontal Cam Lock on Ramp Door
- 48" Heavy Duty Entry Door with Flushlock and Recessed Step
- (1) Non-Powered Vent
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- Back-up Lights
- (2) Deluxe Dome Lights and Switch
- Beavertail
- (4) 5000# Recessed Bolted D-Rings
- Automotive Undercoating
- Limited 3 Year Warranty

[www.cargoexpress.com](http://www.cargoexpress.com)

	<b>PRO-GT RACE TRAILER</b>				
	<b>PRGT8.5X20TE2</b>	<b>PRGT8.5X24TE2</b>	<b>PRGT8.5X24TE3</b>	<b>PRGT8.5X26TE3</b>	<b>PRGT8.5X28TE3</b>
Overall Length	23'11"	27'10"	27'10"	29'10"	31'10"
Width	102"	102"	102"	102"	102"
Height	100"	100"	100"	100"	100"
Interior Length	19'7"	23'7"	23'7"	25'7"	27'7"
Interior Width	96"	96"	96"	96"	96"
Interior Height	78"	78"	78"	78"	78"
Platform Height	19"	19"	19"	19"	19"
Rear Opening Ht.	75"	75"	75"	75"	75"
Rear Opening Wd.	96"	96"	96"	96"	96"
Hitch Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Brakes	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
GVWR	7000#	7000#	9950#	9950#	9950#
Hitch Weight	390#	410#	410#	420#	430#
Curb Weight	3210#	3680#	3680#	3930#	4180#
Payload Capacity	3790#	3320#	6270#	6020#	5770#
Tires	ST205/75R15	ST205/75R15	ST225/75R15	ST225/75R15	ST225/75R15
Wheels	E-COAT	E-COAT	E-COAT	E-COAT	E-COAT
Frame	TUBE	TUBE	TUBE	TUBE	TUBE
Exterior	.040 Screwless	.040 Screwless	.040 Screwless	.040 Screwless	.040 Screwless
One Piece Aluminum Roof	STD	STD	STD	STD	STD
Floor	3/4"	3/4"	3/4"	3/4"	3/4"
Sidewalls	3/8" Wall Liner or White Vinyl	3/8" Wall Liner or White Vinyl	3/8" Wall Liner or White Vinyl	3/8" Wall Liner or White Vinyl	3/8" Wall Liner or White Vinyl
Ceiling	Insul. White Vinyl	Insul. White Vinyl	Insul. White Vinyl	Insul. White Vinyl	Insul. White Vinyl
Tail Lights	LED	LED	LED	LED	LED
Clearance Lights	LED	LED	LED	LED	LED
Dome Light	STD	STD	STD	STD	STD
Switch	STD	STD	STD	STD	STD
Stone Guard	24"	24"	24"	24"	24"
Side Door	48" Heavy Duty	48" Heavy Duty	48" Heavy Duty	48" Heavy Duty	48" Heavy Duty
Ramp	STD	STD	STD	STD	STD
Sand Pad	STD	STD	STD	STD	STD
Crossmembers	16" OC	16" OC	16" OC	16" OC	16" OC
Side Posts	16" OC	16" OC	16" OC	16" OC	16" OC
Roof Bows	16" OC	16" OC	16" OC	16" OC	16" OC
Axles	TORSION	TORSION	TORSION	TORSION	TORSION
EZ Lube	YES	YES	YES	YES	YES
Undercoat	Automotive	Automotive	Automotive	Automotive	Automotive

Specifications Subject to Change Without Notice