



Pro-GT Gooseneck Race Trailer

Specifications vary by plant



STANDARD FEATURES

- Tube Main Frame Construction
- 16" O.C. Frame
- 16" O.C. Tube Sidewalls
- 16" O.C. Roof Bows
- Torsion Axles
- EZ-Lube Hubs
- Electric Brakes
- Radial Tires
- (2) Speed Landing Gear
- Enclosed Landing Gear
- 3/4" Floor
- 3/8" Wall Liner
- White Vinyl Insulated Ceiling Liner
- .040 Screwless Aluminum Exterior
- Two Tone Exterior Available No Charge
- Truck Body Extrusion
- Stainless Steel Front Insert
- Stainless Steel Front Corners
- Stainless Steel Rear Corners and Header
- (1) Piece Aluminum Roof
- Aluminum Fender Flares
- Heavy Duty Ramp Door with Spring Assist & 16" Ramp Door Extension
- Recessed Horizontal Cam Lock on Ramp Door
- 48" Heavy Duty Entry Door with Flushlock and Recessed Step

Shown with Optional Equipment

- Front ATP Access Door
- (1) Non-Powered Vent
- 7-Way Plug
- LED Tail Lights
- LED Clearance Lights
- Back-Up Lights
- (2) Deluxe Dome Lights and Switch
- Beavertail
- (4) 5000# Recessed Bolted D-Rings
- Automotive Undercoating
- Limited 3 Year Warranty

www.cargoexpress.com